

ORGATEX®

Technical Data Sheet LongLife®

Floor Markings Tapes, Symbols, Clearview, Floor Signs and Heavy Duty

PRODUCT/APPLICATION DESCRIPTION:

- High-quality PVC with a special adhesive on an acrylate basis (modified) ensures
- Easy processing out of a dispenser box (Tapes)
- Forklift truck resistance
- High abrasion strength
- Excellence adhesion on almost all underground
- Plasticizer resistance
- Cleaning machine resistance
- Free of silicone

USE:

- Marking of storage positions
- Marking of drive- and walkways
- Identification of danger areas
- Implementation of 5S projects

TECHNICAL DATA:

- Optimal Application Temperature 18- 25 degrees C
- Suitable range for industrial use
- Withdrawal (DIN 53377) <1.5% at 10 min. 80C
- Chemical Resistance
- Adhesive strength on average 10.8 N/cm
- Wear Resistance (UV)
- Resistance to moisture
- Temperature resistance 70C (short-term)
- Temperature resistance 60 degrees C (long-term)
- Silicone-free

USE INSTRUCTIONS:

The surface must be dry, clean and free of dust, oil, grease and solvent (We recommend to use our LongLife Cleaner for the preprocessing). Loose coatings need to be removed or tightened before starting the processing. After adhesive bonding the LongLife should be strained to raise the stability

WARRANTY AND RESPONSIBILITY:

Our information and references are based on the standard of knowledge. The stated values in our data sheets are typical or average values. Changings or amendments are possible at any time. The application is out of our scope of influence so that we couldn't assume any liabilities or guarantee. We recommend and provide samples for testing.

LeanProducts srl | 33170 Pordenone Via Bassani, 8 | Tel. 0434.572757 r.a.
C.F./P.Iva: 01640790935 | E-mail: info@LeanProducts.eu | Web: www.LeanProducts.eu