

## LP-C0021



<b>Design</b>	
<b>Material</b>	
Seat / Backrest	PUR integral foam / PUR integral foam
Five star base xx20 Ø655mm with dual castors (Ø 65mm)	diecast aluminium unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated
Backrest steel bar	high-precision steel bar, Ø26 x 1,5mm
<b>Total height *</b>	745 to 1020mm
<b>Thickness of seat / backrest *</b>	35mm / 35mm
<b>Weight *</b>	11.30kg
<b>Loading capacity</b>	120kg
<b>Adjustabilities</b>	
Seat height (acc. DIN 68877) *	460 to 640mm
Seat tilt *	-4° to +10°
Seat lock	continuous
Backrest tilt *	-10° to +8°
<b>Details</b>	
<b>Backrest</b>	
Width *	420mm
Height *	300mm
<b>Seat</b>	
Width *	460mm
Depth *	435mm
<b>Characteristics</b>	
Conductivity	10 <sup>4</sup> Ohm to 10 <sup>6</sup> Ohm acc. EN 61340-5-1-1

\*: production- or model-related differences are possible

Revision status 10.03.2016

We are constantly developing our products for you in design as well as in quality. Please contact us about your special requirements for work places and employees. We offer you individual solutions for special seat and standing work places.

